

# USD 20-25/55 Buried clamp double

## 12180

CE 6/2022

### Areas of application:

For the simple plaster laying of flexible pipes on hollow brick, for laying two pipes.

### Installation Guide:

- Drill a 6 mm Ø hole
- Insert flexible pipes on both sides of the USD
- Stretch the flexible pipes
- Insert the USD into the drill-hole

### Product details:

Colour	light grey
Content pack/box	100 / 2.400
Clamping range	20-25
Pipe dimension	
Dowel length in mm	55

### Mounting and usage instructions:

Use the LB lance drill – indispensable for the perfect flush mounting – drill an exact hole in the hollow brick. Two pipes / tubes are mounted at the same time using the USD – with just one drill hole. The clamp is available in two dimensions and is suitable for holding two pipe spans or tubes, for example the USD 20-25 can hold both a size 20 or a size 25.

### Product benefits/properties:

The integrated nib on the inside of the clamp allows the pipe to be spanned for easier wiring.

### Technical data:

Material	PP Temperature range: -10 °C up to +85 °C silicon-free LSFOH halogen-free low-smoke tested according to OVE guideline R14
----------	--

Weight per piece 2,30 g

GTIN (EAN)



Two pipes are mounted at the same time with the USD with just one borehole. And thanks to the integrated nib on the interior clip side, the pipe can be tensed for easier cable insertion.



Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria  
Telephone +43 2742 22167-0. office@schnabl.works. www.schnabl.works

