USA 16-20/11 automatic buried clamp

12330

(E22

Areas of application:

For the simple plaster laying of flexible pipes on plasterboard.

Installation Guide:

- Drill a 6 mm Ø hole
- Insert the USA in the drill-hole
- Insert flexible or rigid pipe into the USA and push down until it closes automatically

Product details:

| | Colour | light grey |
|--|----------------------------------|-------------|
| | Content pack/box | 100 / 3.200 |
| | Clamping range Pipe dimension | 16-20 |
| | Dowel length in mm | 11 |

Mounting and usage instructions:

The USA automatically closes around the laid pipe. This clip is available in four ranges, but all are suitable for holding two pipe dimensions. For example the USA 20-25 can hold both a size 20 or a size 25 pipe. The USA can easily be opened without a tool.

Product benefits/properties:

USA is a buried clamp for flexible pipes and tubes. For flush surface mounting. Saves you time!

Technical data:

| Material | PP Temperature range: -10 °C up to +85 °C silicon-free LSF0H halogen-free low-smoke tested according to OVE guideline R14 |
|------------------|---|
| Weight per piece | 1,50 g |
| Max. reccd. load | Reference value: USA 20-25/25: 96.56 N concrete, 84.08 N solid brick, 93.88 N hollow brick, 42.64 N aerated Concrete, 76.48 N plasterboard |
| Breaking load | Reference value: USA 20-25/25: 241.40 N (24 kg) concrete, 210.20 N (21 kg) solid brick, 234.70 N (23 kg) hollow brick, 106 N (10 kg) aerated concrete, 191 N (19 kg) plasterboard |
| GTIN (EAN) | |





An innovative product for sub-plaster mounting - the Buried Clamp Automatic USA. A quick push is enough to affix the clamp to the pipe.







