USA 16-20/11 automatic buried clamp

12330

Areas of application:

For the simple plaster laying of flexible pipes on plasterboard.

Installation Guide:

- Drill a 6 mm Ø hole
- Insert the USA in the drill-hole
- · Insert flexible or rigid pipe into the USA and push down until it closes automatically

Product details:

Colour	light grey
Content pack/box	100 / 3.200
Clamping range Pipe dimension	16-20
B 11 11 1	11

Dowel length in mm 11

Mounting and usage instructions:

The USA automatically closes around the laid pipe. This clip is available in four ranges, but all are suitable for holding two pipe dimensions. For example the USA 20-25 can hold both a size 20 or a size 25 pipe. The USA can easily be opened without a tool.

Product benefits/properties:

USA is a buried clamp for flexible pipes and tubes. For flush surface mounting. Saves you time!

Technical data:

	•
Material	PP Temperature range: -10 °C up to +85 °C silicon-free halogen-free
Weight per piece	1,50 g
Max. reccd. load	Reference value: USA 20-25/25: 170 N (17 kg) concrete, 150 N (15 kg) solid brick, 160 N (16 kg) hollow brick, 75 N (7.5 kg) aerated Concrete, 130 N (13 kg) plasterboard
Breaking load	Reference value: USA 20-25/25: 241.40 N (24 kg) concrete, 210.20 N (21 kg) solid brick, 234.70 N (23 kg) hollow brick, 106 N (10 kg) aerated concrete, 191 N (19 kg) plasterboard
GTIN (EAN)	9 008439 123308













