



TRIPLE POWER 3.0 BATTERY

- Systematic design, in-depth optimization and seamless connection with Solax Hybrid inverter
- Safest type of LiFePO₄ battery, an adoption of high-performance processors, international brand devices, better stability
- Unique battery heating technology, which is capable to work at low temperature
- Long life cycle, more than 6000 times
- Safety Cert. TUV, CE, UL, UN38.3 and so on
- Remote fault diagnosis, upgrade and maintenance
- Auto power replenishment technology is adopted to prevent battery over-discharge
- Multiple communication interfaces :RS485, CAN
- Modular stacking design, easy installation, supporting floor and wall mounting
- IP65, supporting indoor and outdoor installation



	T-BAT-SYS-HV-3.0	T-BAT-SYS-HV-6.0	T-BAT-SYS-HV-9.0	T-BAT-SYS-HV-12.0
Nominal voltage [V]	102.4	204.8	307.2	409.6
Operating voltage range [V]	90~116	180~232	270~348	360~464
Total energy [kWh]	3.0	6.1	9.2	12.2
Usable energy ¹⁾ [kWh]	2.7	5.5	8.3	10.9
Rated capacity [Ah]			30	
Nominal power [kW]	2.5	5.1	7.6	10.2
Max. power [kW]	3.0	6.1	9.2	12.2
Recommend charge/discharge current [A]			25	
Max. charge/discharge current [A]			30	
Battery roundtrip efficiency			95%	
Cycle life [90% DOD]			6000 Cycles	
Expected life time / Warranty [year]			10	
Available charge/discharge temperature range [°C]			-30 to 50	
Storage temperature [°C]			-20 to 50 (3 months)	
Relative humidity [%]			0~100	
Altitude [m]			Below 3000	
Degree of protection			IP65	
Battery to Inverter			RS485/CAN2.0	
Battery to battery/BMS			CAN2.0	
Master control capacity indicator			4LED (25%, 50%, 75%, 100%)	
Master control LED indicator (Working mode)			1 LED	
System switch (on/off)			Buttonx1+Breakerx1	
Certificate			CE/IEC62619/UN38.3/IEC62040/UKCA	
Hazardous materials classification			Class 9	
Dimensions(WxHxD) [mm]			MC0600: 482.5x173.5x153 HV10230: 482.5x471.5x153	
Net weight [kg]	MC0600: 7.5kg +HV10230: 34.5kg	MC0600: 7.5kg +2xHV10230: 69kg	MC0600: 7.5kg +3xHV10230: 103.5kg	MC0600: 7.5kg +4xHV10230: 138kg

[1] Test conditions:90% DOD, 0.2C charger & discharger @+25°C
 * MC0600:Master Box (one MC0600 can be connected 1~4 HV10230)
 * HV10230:Slave Battery Pack
 * Max charge/discharge current may be variant with different inverter models

V2.0. Information may be subject to modify without notice.
 650.00011.00