

SPG DCA IT LRM (767 122)

- Nominal voltages up to 45 kV / 50 Hz (three-phase systems)
- Indication by two separate LEDs
- Automatic deactivation



Figure without obligation




Figure without obligation

| Type | SPG DCA IT LRM |
|---|---|
| Part No. | 767 122 |
| Nominal voltage (U _n) | 1 ... 45 kV |
| Frequency | 50 Hz |
| Dimensions | 120 x 60 x 25 mm |
| Plug spacing | 14 mm |
| Type of plug | 2 multilam plugs (Ø4 mm) |
| Input impedance (LRM system) | 2 MOhms |
| Test threshold | 3.2 µA |
| Standard | EN/IEC 61243-5 (DIN VDE 0682-415) |
| Temperature range | -25 °C ... +55 °C |
| Type of device | Interface test unit |
| Use | Active indicator for maintenance test of coupling systems |
| Indication | Visual |
| Type of system | LRM |
| Self-testing element | Yes |
| Weight | 185 g |
| Customs tariff number (Comb. Nomenclature EU) | 90303320 |
| GTIN | 4013364074385 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.