

## APT ID 54 (785 344)



Figure without obligation

| Type   | APT ID 54   |
|--|---|
| Part No.   | 785 344 <b>NEW</b>  |
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole) | APC 2   |
| Arc energy ( $W_{arc}$ or $W_{LBP}$ )                            | 320 kJ  |
| Arc Rating – ATPV (Open Arc)                                     | 18 cal / cm <sup>2</sup> *)   |
| Arc Rating – ELIM (Open Arc)                                     | 13 cal / cm <sup>2</sup>  |
| PPE category (NFPA 70E)  | PPE 2   |
| Material   | Cotton (52%), modacrylic (22%), viscose (19%), para-aramid (6%), static inhibitors (1%) |
| Weight per unit area   | 450 g/m <sup>2</sup>  |
| Material (sewing thread)   | Kevlar (100%)   |
| Standard   | IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 13688, EN ISO 11611, EN 17353              |
| Primary colour   | grey  |
| Secondary colour   | black   |
| Zipper   | red   |
| Size (international)   | 54 (L)  |
| Design code  | TIGRBLRE0000P0  |
| Weight   | 950 g   |
| Customs tariff number (Comb. Nomenclature EU)                    | 62034211  |
| GTIN   | 4013364452022   |
| PU   | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.