

APJ OD YE 52 (785 353)



Figure without obligation

| Type | APJ OD YE 52 |
|--|--|
| Part No. | 785 353 ^{new} |
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole) | APC 2 |
| Arc energy (W_{arc} or W_{LBP}) | 320 kJ |
| Arc rating – ATPV (open arc) | 16 cal / cm ² *) |
| Arc rating – ELIM (open arc) | 13 cal / cm ² |
| PPE category (NFPA 70E) | PPE 2 |
| Material | Modacrylic (40%), viscose (59%), static inhibitors (1%), PU membrane: meta-armid knitting (100%) |
| Weight per unit area | 300 g/m ² |
| Material (sewing thread) | Kevlar (100%) |
| Standard | IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471, EN 13034, EN ISO 13688, EN ISO 11611 |
| Primary colour | fluorescent yellow |
| Secondary colour | grey |
| Zipper | red |
| Size (international) | 52 (M/L) |
| Design code | JOYEGRRE0000P0000 |
| Weight | 815 g |
| Customs tariff number (Comb. Nomenclature EU) | 62033911 |
| GTIN | 4013364452107 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.