

## APJ OD OG 48 (787 351)



Figure without obligation

Type	APJ OD OG 48
Part No.	787 351 <small>new</small>
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy ( $W_{arc}$ or $W_{LBP}$ )	320 kJ
Arc rating – ATPV (open arc)	16 cal / cm <sup>2</sup> *)
Arc rating – ELIM (open arc)	13 cal / cm <sup>2</sup>
PPE category (NFPA 70E)	PPE 2
Material	Modacrylic (40%), viscose (59%), static inhibitors (1%), PU membrane: meta-armid knitting (100%)
Weight per unit area	300 g/m <sup>2</sup>
Material (sewing thread)	Kevlar (100%)
Standard	IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471, EN 13034, EN ISO 13688, EN ISO 11611
Primary colour	fluorescent orange
Secondary colour	grey
Zipper	red
Size (international)	48 (S)
Design code	JOORGRE0000P0000
Weight	811 g
Customs tariff number (Comb. Nomenclature EU)	62033911
GTIN	4013364478176
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.