

APJ OD OG 52 (787 353)



Figure without obligation

Type	APJ OD OG 52
Part No.	787 353 ^{NEW}
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W _{arc} or W _{LBP})	320 kJ
Arc rating – ATPV (open arc)	16 cal / cm ² *)
Arc rating – ELIM (open arc)	13 cal / cm ²
PPE category (NFPA 70E)	PPE 2
Material	Modacrylic (40%), viscose (59%), static inhibitors (1%), PU membrane: meta-armid knitting (100%)
Weight per unit area	300 g/m ²
Material (sewing thread)	Kevlar (100%)
Standard	IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471, EN 13034, EN ISO 13688, EN ISO 11611
Primary colour	fluorescent orange
Secondary colour	grey
Zipper	red
Size (international)	52 (M/L)
Design code	JOORGRE0000P0000
Weight	815 g
Customs tariff number (Comb. Nomenclature EU)	62033911
GTIN	4013364478190
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.